



FXCS-1B13-C-MI - FXCS Series, Seal-XM, Iron Dead-End Momentary Contact Single Push Button & Pilot Light Ctrl Station, 1/2" Hub, Red Button, Clear Lens

By Killark
Catalog # [FXCS-1B13-C-MI](#)

FXCS Series - Seal-XM - Iron Dead-End Momentary Contact Single Push Button and Pilot Light Control Station - Factory Sealed - 1/2" Hub - Red Button - Clear Lens

Features

- Incorporates Factory Sealed Universal contact blocks and GOB3 LED pilot light devices.
- External sealing fittings typically not required, reducing installation time and cost.
- No seal plate between the electrical device and back box allows direct wiring to contact terminals.
- NEMA 3 weatherproof.
- Grounding boss supplied in the splice box.
- Sold as a complete unit.
- Standard finish is a gray epoxy powder baked on for ultimate corrosion resistance.
- More wiring room in back box.

Application

SEAL-XM Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
CSA File Number	LR11714, 2493125



Buy America(n) Qualified Contact Manufacturer

Configuration

Back Box Type FXB
Hub Pattern Dead-End

Current

Amperage Rating 10 A
Frequency Rating 50/60 Hz

Dimensions

Depth 4.59 in
Hub Size 1/2"

General

Type Factory Sealed
Series FXCS Seal-XM Series
UPC 783936104911
Color Red P.B., White Light

Logistics

Factory Sealed Factory Sealed

Operational

Action Momentary
Actuator Pilot Light & Pushbutton

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)