



GCS Series - Aluminum Operator Body - Three Drilled And Tapped Operator Holes In Back Of Box - Style 2

By Killark
Catalog # [GCS-163](#)

GCS Series - Aluminum Operator Body - Three Drilled And Tapped Operator Holes In Back Of Box - Style 2

Features

- Device bodies and covers are cast copperfree aluminum alloy and provide a wide assortment for custom assemblies.
- Bodies are designed for custom drilled and tapped conduit openings on all four sides and the back.
- Ground flange joint between bolted cover and box provide required flame path.
- GO Short Style Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.
- Open space between gangs for easy wiring from one cover to another.
- Contact blocks are rated heavy duty, 600 VAC max.
- Internal ground screw.

Application

For use with G Series custom control panel operators.

Specifications

Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G
---------------------	---



EU RoHS Indicator	• Class III, Divisions 1 & 2
UL File Number	Contact Manufacturer
CSA File Number	E10514
Buy America(n) Qualified	LR11716
	Contact Manufacturer

Configuration

Back Box Type	SWB
---------------	-----

Dimensions

Gross Weight with Packaging	7.8
Depth	4-1/4 in

General

Type	Aluminum Operator Body
Series	GCS Series
UPC	783936205366
Color	Gray

Logistics

Carton Quantity	2
-----------------	---

Product Assets

[Catalog \[English\]](#)