



# HKH Series Control Station, Spring Returned 3 Position Selector Switch- Return to Center from Left- Din Rail Mount- 3/4" Hub - Stainless Steel 1a

By Killark  
Catalog # [HKH1ASD2S640K8](#)

HKH Spring Returned 3 Position Selector Switch- Return to  
Center from Left- Din Rail Mount- 3/4" Hub - Stainless Steel 1a

## Features

- Size 1 Control Stations available as 1a, 1b, & 1c as standard catalog number offerings for 1, 2 & 3 device openings and will accept 2-M20 entries in either end.
- Ammeters available in 1b & 1c.
- Size 2 Enclosures available as 2a & 2c for 2, 4 & 6 device entries in cover with ability to accept 2-M25 entries in either end.
- Operating Temperature of -50°C to +60°C.
- Explosion Protected contact blocks 690 VAC N.O. & N.C. capable of 20 Amps for Switching Duty and HP Ratings up to 1HP.
- LED Pilot Light modules for 12-250V AC/ DC for UL applications. 12-254V AC/DC for IEC applications.
- Contacts & Pilot lights can be mounted inside enclosure on Din Rail or in cover to the actuator.
- Accessories available for Lockout/Tag Out functions made in 316 stainless steel.

## Application

Hazardous and corrosive environments due to the presence of flammable gases or vapors, combustible dusts or ignitable fiber or flyings, Installations at petroleum refineries, chemical and petrochemical plants and other processing or storage facilities where similar hazards exist, Use in conjunction with motor starters or contactors for remote control of motors

## Specifications

|                     |                                                                                                                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazardous Rating(s) | <ul style="list-style-type: none"><li>• Class I, Division 2, Groups A, B, C, D</li><li>• Class II, Division 1, Groups E, F, G (Canada Only)</li><li>• Class II, Division 2, Groups E, F, G</li><li>• Class III, Divisions 1 &amp; 2</li></ul> |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



|                          |                      |
|--------------------------|----------------------|
| IECEx File Number        | • Zones 1 & 2        |
| EU RoHS Indicator        | • Zones 21 & 22      |
| Nema Rating              | 15.0054X             |
| UL File Number           | Contact Manufacturer |
| Buy America(n) Qualified | 3, 4, 4X, 12, 13     |
| ATEX File Number         | E53360               |
|                          | Contact Manufacturer |
|                          | 1405X                |

## Current

|                  |          |
|------------------|----------|
| Amperage Rating  | 20 A     |
| Frequency Rating | 50/60 Hz |

## Dimensions

|          |          |
|----------|----------|
| Depth    | 4.16 in  |
| Hub Size | 3/4"     |
| Weight   | 1.22 lb. |

## General

|               |                           |
|---------------|---------------------------|
| Series        | HKH Series                |
| Material      | Stainless Steel, Type 316 |
| UPC           | 783936127415              |
| Color         | Black                     |
| Mounting Type | Wall                      |

## Operational

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -50°C to 60°C              |
| Celsius                     |                            |
| Action                      | Momentary Left             |
| Actuator                    | 3 Position Selector Switch |
| Horsepower - Maximum        | 1                          |

## Product Assets

[Catalog \[English\]](#)  
[Installation Manual \[English\]](#)