


200 Series

C A R T O N S E A L I N G T A P E

Venture Tape 200 is a strong, thin polypropylene film tape coated with a high grade natural rubber pressure sensitive adhesive (PSA). Specifically designed for carton sealing and corrugated packaging applications, Venture Tape 200 has excellent performance over a wide range of temperatures and environmental conditions.

Product Construction



Features & Benefits

- Versatile packaging tape product meets a wide variety of application requirements
- Humidity and environmental condition resistance
- Excellent performance at high and low temperatures
- Durability under stress
- In-stock product available for immediate shipment

Test	Typical Value	Test Method
Product Thickness (total)	2.3 mils	PSTC-133
Carrier Thickness	1.0 mils	PSTC-133
Adhesive Thickness	1.3 mils	PSTC-133
Peel Adhesion	33 oz/in	PSTC-101
Shear Strength	>24 hours	PSTC-107
Tensile Strength	25 lb/in width	PSTC-131
Elongation	142 %	PSTC-131
Application Temperature	40 °F to 100 °F	
Service Temperature	-10 °F to 212 °F	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

Width (in.)	Length (LY)	Rolls/Case
2	55	36
3	55	24

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

splicing@venturetape.com



North American Warehouse Locations

Randolph, MA

Elk Grove Village, IL

Houston, TX

Walnut, CA

Brampton, Ontario

Lawrenceville, GA

Milwaukee, WI

Lewisville, TX

Tualatin, OR

Lachine, Quebec

Venture Tape Corp.

30 Commerce Road

Rockland, MA 02370

781-331-5900

781-871-0065 FAX

www.venturetape.com