

## PowerPoint PP-B-2,5t-3/4"-10UNC

Artikel-Nr: 8600593




- **Double ball bearing** is the optimal solution for turning and flipping operations under full load (not suitable for permanent turning under load).
- **Lifting points pivots 360°.**
- **Large distance between bolt-on surface and load to avoid damage.**
- **Rotatable at nominal WLL, 90° to the bolt-on direction** Lowest kinking possibility due to cardan joint.
- **Suspension ring with enlarged pivoting area.**
- Clear marking of the minimum WLL for all loading directions.
- Marking with requested torque moment and nominal WLL with a safety factor of 4:1 (MRL 2006/42/EG) and 5:1 (ASME B 30.26).
- Component according to the test criterias of BG/DGUV "GS-HM 36".
- Significant product characteristics of the PP-S, PP-B and PP-VIP are subject to property right claims. ● Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

## PowerPoint PP-B-2,5t-3/4"-10UNC

Artikel-Nr: 8600593



<b>weight</b>	1.10 kg	2.43 lbs
<b>Nominal WLL</b>	2500 kg	5500 lbs
<b>T</b>	136 mm	5-11/32"
<b>A</b>	13 mm	1/2"
<b>B</b>	75 mm	2-15/16"
<b>C</b>	40 mm	1-9/16"
<b>D</b>	61 mm	2-13/32"
<b>E</b>	55 mm	2-5/32"
<b>F</b>	30 mm	1-3/16"
<b>G</b>	61 mm	2-13/32"
<b>M</b>	3/4"-10UNC mm	3/4"-10UNC
<b>N</b>	18 mm	23/32"