



Main

Range of product	Altivar
Product or component type	Encoder interface module
Range compatibility	Altivar 32 Altivar Machine ATV320
[Us] rated supply voltage	5 V 5...5.5 V)
Number of pulses per revolution	3600 ATV32

Complementary

Product compatibility	ATV32 >= V1.8)
Protection type	Overload protection Short-circuit protection
Maximum operating frequency	250 kHz
Input signal	TTL
Electrical connection	Terminal 1.5 mm ² AWG 16), encoder, 200 mA
Net Weight	0.66 lb(US) (0.3 kg)

Ordering and shipping details

Category	18297 - LEXIUM 32 DRIVES ACCESSORIES
Discount Schedule	PC51
GTIN	00785901946953
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.85 in (4.7 cm)
Package 1 width	2.56 in (6.5 cm)
Package 1 Length	3.54 in (9 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration