

References

Single PV circuit 750 VDC - Back plate mounting

Rating (A)	Circuit type	Number of poles of the device	Number of pole(s) in series per polarity	Switch body	Direct handle ⁽²⁾	External handle	Shaft for external handle	Bridging bars
100 A	Single PV circuit	3 P	2P+, 1P-	26PV 3010	J1 type Black 1112 1111 ⁽¹⁾ Red 1113 1111	S2 type Black IP55 1421 2111 ⁽¹⁾ Black IP65 1423 2111 Red IP65 1424 2111	200 mm 1400 1020 320 mm 1400 1032 ⁽¹⁾ 500 mm 1400 1050	2609 0025
125 A								
160 A								
200 A								
250 A								
315 A								
400 A								
500 A								
630 A								
800 A								
1000 A								
1250 A								
1600 A								
2000 A								
2500 A								
3200 A								

(1) Standard.

(2) Other types of operation handle available. see "Accessories" pages.

Dual PV circuit 750 VDC - Back plate mounting

Rating (A)	Circuit type	Number of poles of the device	Number of pole(s) in series per polarity	Switch body	Direct handle ⁽²⁾	External handle	Shaft for external handle	Bridging bars							
100 A	Dual PV circuit	6 P	2x (2P+, 1P-)	26PV 6010	J3 type Black 1132 1111 ⁽¹⁾ Red 1133 1111	S3 type Black IP55 1431 3111 ⁽¹⁾ Black IP65 1433 3111 Red IP65 1434 3111	200 mm 1401 1520 320 mm 1401 1532 ⁽¹⁾ 400 mm 1401 1540	2 x 2609 0025							
125 A															
160 A															
200 A															
250 A															
315 A															
400 A															
500 A															
630 A															
800 A															
1000 A															
1250 A															
1600 A															
2000 A															
											Please consult us				2 x 2609 0080
											26PV 6100	J4 type Black 1142 1111 ⁽¹⁾ Red 1143 1111	S4 type Black IP65 1443 3111 ⁽¹⁾ Red IP65 1444 3111	200 mm 2799 3015 320 mm 2799 3018 ⁽¹⁾ 450 mm 2799 3019	2 x 2609 1100
											26PV 6120				
				26PV 6160	V1 type Black 2799 7074	S5 type Black IP65 1453 8111 Red IP65 1454 8111		2 x 2609 1200							
				26PV 6200											

(1) Standard.

(2) Other types of operation handle available. see "Accessories" pages.