

References

NFC and DIN - Front operation - Switch body with a shunt trip coil - 230 VAC

Rating (A) / Fuse ⁽⁴⁾	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	1 st position AC	Tripping AC	Terminal shrouds top	Terminal screens top	Inter phase barrier																												
630 A / 3	3 P	3520 3063	Black 3999 6203 ⁽¹⁾	S3 type Black IP55 1431 3511 ⁽¹⁾ Red IP55 1432 3511	320 mm 1401 1532	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3998 3063	3 P 2998 3120 ⁽²⁾ 4 P 2998 4120 ⁽²⁾	3 P 2998 0003 4 P 2998 0004																												
	4 P	3520 6063						3998 4063																														
800 A / 4	3 P	3520 3080						Black 3999 6203 ⁽¹⁾			S3 type Black IP55 1431 3511 ⁽¹⁾ Red IP55 1432 3511	320 mm 1401 1532	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3 P 2998 3120 ⁽²⁾ 4 P 2998 4120 ⁽²⁾	3 P 2998 0003 4 P 2998 0004																						
	4 P	3520 6080															3 P 2998 3180 ⁽²⁾ included 2998 4180 ⁽²⁾																					
1250 A / 4	3 P	3520 3120																Black 3999 6203 ⁽¹⁾	S3 type Black IP55 1431 3511 ⁽¹⁾ Red IP55 1432 3511	320 mm 1401 1532	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3 P 2998 3120 ⁽²⁾ 4 P 2998 4120 ⁽²⁾	3 P 2998 0003 4 P 2998 0004														
	4 P	3520 6120																																				
1600 A / 2 x 4*	3 P	3520 3160																							Black 3999 6203 ⁽¹⁾	S3 type Black IP55 1431 3511 ⁽¹⁾ Red IP55 1432 3511	320 mm 1401 1532	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3 P 2998 3120 ⁽²⁾ 4 P 2998 4120 ⁽²⁾	3 P 2998 0003 4 P 2998 0004							
	3 P + NC	3520 4160																																				
	4 P	3520 6160																																				
1800 A / 2 x 4*	3 P	3520 3180 ⁽³⁾																														Black 3999 6203 ⁽¹⁾	S3 type Black IP55 1431 3511 ⁽¹⁾ Red IP55 1432 3511	320 mm 1401 1532	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3 P 2998 3120 ⁽²⁾ 4 P 2998 4120 ⁽²⁾	3 P 2998 0003 4 P 2998 0004
	3 P + NC	3520 4180 ⁽³⁾																																				
	4 P	3520 6180 ⁽³⁾																																				

(1) Standard.

(2) Bottom terminals protection screen as standard.

(3) Only one of the two T4 fuses should be equipped with striker.

(4) For the fuses: see page 236 "NFC-DIN industrial fuselinks 0.16 to 1250 A".

* Two size 4 DIN fuses in parallel per pole.