

NFC and DIN - Direct operation - 160 to 400 A

Rating (A) Fuse size Frame size	No. of poles	Direct side operation	Direct front operation	Direct handle	Auxiliary contacts	Terminal shrouds	Cage terminals	Lock for fuse protection cover	Handle key interlocking accessories ⁽⁵⁾		
160 A 00 3	2 P	3615 2015	consult us	Black 3629 7901 ⁽⁴⁾⁽¹⁾		2 P 3998 2016 ⁽³⁾	3 P 5400 3016	3999 8912	3629 7913		
	3 P	3615 3015	consult us			3 P 3998 3016 ⁽³⁾				4 P 5400 4016	3999 8216
	4 P	3615 6015	consult us			4 P 3998 4016 ⁽³⁾				4 P 5400 4016	3999 8316
160 A 0 4	2 P	3615 2016	consult us	Black 3629 7901 ⁽⁴⁾⁽¹⁾	A-type 1 contact NO/NC 3999 0022 ⁽²⁾	2 P 3998 2025 ⁽³⁾	3 P 5400 3025 4 P 5400 4025	3999 8225			
	3 P	3615 3016	consult us					3999 8325			
	4 P	3615 6016	consult us					3999 8425			
250 A 1 5	2 P	3615 2024	consult us	Black 3629 7901 ⁽⁴⁾⁽¹⁾	A-type 2 contacts NO/NC 3999 0022 ⁽²⁾	3 P 3998 3025 ⁽³⁾	3 P 5400 3040 4 P 5400 4040	3999 8240			
	3 P	3615 3024	consult us					3999 8340			
	4 P	3615 6024	consult us					3999 8440			
400 A 2 6	2 P	3615 2039	consult us	Black 3629 7901 ⁽⁴⁾⁽¹⁾		4 P 3998 4025 ⁽³⁾	3 P 5400 3040 4 P 5400 4040	3999 8240			
	3 P	3615 3039	consult us					3999 8340			
	4 P	3615 6039	consult us					3999 8440			

(1) Standard.

(2) Maximum 2 contacts.

(3) Top/bottom.

(4) Direct right side operation.

(5) Locking using RONIS EL11AP lock (lock not included).

NFC and DIN - Direct operation - 630 to 1250 A

Rating (A) Fuse size Frame size	No. of poles	Direct side and front operation	Direct front handle	Direct side handle	Auxiliary contacts	Terminal shrouds
630 A 3 17	2 P	3811 2063	Black 3899 6011 ⁽¹⁾⁽²⁾			2 P 3898 2080 ⁽³⁾
	3 P	3811 3063				3 P 3898 3080 ⁽³⁾
	4 P	3811 6063				4 P 3898 4080 ⁽³⁾
800 A 3 17	2 P	3811 2080	Black 3899 7911		U-type 1 contact NO 3999 0701 ⁽⁴⁾	3999 8216
	3 P	3811 3080				3999 8316
	4 P	3811 6080				3999 8416
800 A 4 18	2 P	3811 2081	Black 3899 7011 ⁽¹⁾⁽²⁾		1 contact NC 3999 0702 ⁽⁴⁾	2 P 3898 2120 ⁽³⁾
	3 P	3811 3081				3 P 3898 3120 ⁽³⁾
	4 P	3811 6081				4 P 3898 4120 ⁽³⁾
1250 A 4 18	2 P	3811 2120	Black 3899 7011 ⁽¹⁾⁽²⁾			2 P 3898 2120 ⁽³⁾
	3 P	3811 3120				3 P 3898 3120 ⁽³⁾
	4 P	3811 6120				4 P 3898 4120 ⁽³⁾

(1) Direct front operation.

(2) Standard.

(3) Top/bottom.

(4) Maximum 8 contacts.