

FUSERBLOC

Fuse combination switches

for industrial fuses up to 1250 A

References (continued)

BS 88 - Direct operation - 20 to 160 A

| Rating (A) Fuse size Frame size | Number of poles | Reference Side direct operation | Reference Direct front operation | Side direct handle | Direct front handle | Auxiliary contacts | Terminal shrouds ⁽³⁾ | Cage terminals | Handle key interlocking accessories ⁽²⁾ | | | | | | |
|-----------------------------------------|---------------------------|---------------------------------------|----------------------------------------|-----------------------|------------------------|----------------------------------------------------------|------------------------------------|-------------------|----------------------------------------------------------|--|-----------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------|-----------|--|
| 20 A A1 0 | 3 P | | 3641 3000 | | Black 3629 4012 | 1 contact NO/NC A-type 3999 0001 ⁽¹⁾ | | | | | | | | | |
| | 3 P + switched neutral | | 3641 4000 | | | | | | | | | | | | |
| | 3 P + solid neutral | | 3641 5000 | | | | | | | | | | | | |
| CD 32 A A1 0 | 3 P | | 3641 3001 | | | | | | | | 2 contacts NO/NC A-type 3999 0002 ⁽¹⁾ | Standard | Standard | | |
| | 3 P + switched neutral | | 3641 4001 | | | | | | | | | | | | |
| | 3 P + solid neutral | | 3641 5001 | | | | | | | | | | | | |
| 32 A A1 1 | 2 P | 3625 2003 | consult us | Black 3629 7900 | | | | | 3629 7903 | | | | | | |
| | 3 P | 3625 3003 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6003 | consult us | | | | | | | | | | | | |
| 63 A A2-A3 2 | 2 P | 3625 2006 | consult us | | | | | | | | | | | | |
| | 3 P | 3625 3006 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6006 | consult us | | | | | | | | | | | | |
| 100 A A4 ⁽⁴⁾ 3 | 2 P | 3625 2010 | consult us | Black 3629 7901 | | 1 contact NO/NC A-type 3999 0021 ⁽¹⁾ | | | | | | | | | |
| | 3 P | 3625 3010 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6010 | consult us | | | | | | | | | | | | |
| CD 160 A A3-A4 ⁽⁴⁾ 3 A | 2 P | 3625 2014 | consult us | | | | | | | | 2 contacts NO/NC A-type 3999 0022 ⁽¹⁾ | 2 P 3998 2016 3 P 5400 3016 3998 3016 4 P 5400 4016 3998 4016 | 3 P 5400 3016 4 P 5400 4016 | 3629 7913 | |
| | 3 P | 3625 3014 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6014 | consult us | | | | | | | | | | | | |
| 160 A A4 4 | 2 P | 3625 2015 | consult us | | | | | | | | | | | | |
| | 3 P | 3625 3015 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6015 | consult us | | | | | | | | | | | | |
| 160 A B1-B2 4 | 2 P | 3625 2016 | consult us | | | | | | | | | | | | |
| | 3 P | 3625 3016 | consult us | | | | | | | | | | | | |
| | 4 P | 3625 6016 | consult us | | | | | | | | | | | | |

(1) Max. 2 contacts.

(2) Lock not included.

(3) Top/bottom.

(4) For fuse size A4: max diameter 31 mm.