

NFC and DIN - Side operation - Switch body with a shunt trip coil - 230 VAC

Rating (A) Fuse	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	Auxiliary contact position	Auxiliary contact tripping	1 st Fuse blown AC	Terminal shrouds (1 piece)	Terminal screens top	Inter phase barrier					
250 A / 1	3 P	3655 3026	Black 3999 6012 ⁽¹⁾	S3 type Black IP55 1435 3511 ⁽¹⁾ S3 type Red IP55 1436 3511	200 mm 1403 1520	1 st contact NO/NC 3999 0051 2 nd contact NO/NC 3999 0052	1 contact NO/NC 3999 0031	3 P 3994 1304	3 P 3998 3040 ⁽²⁾							
	4 P	3655 6026														
400 A / 2	3 P	3655 3041											4 P 3994 1404	4 P 3998 4040 ⁽²⁾		
	4 P	3655 6041														
630 A / 3	3 P	3655 3064											3994 1306	3998 3063 ⁽²⁾		
	4 P	3655 6064											3994 1406	3998 4063 ⁽²⁾		
800 A / 4	3 P	3655 3080														
	4 P	3655 6080											3 P 3994 1312		3 P 3998 3120 ⁽³⁾	3 P 2998 0003
1250 A / 4	3 P	3655 3121											4 P 3994 1412		4 P 3998 4120 ⁽³⁾	4 P 2998 0004
	4 P	3655 6121														

(1) Standard.

(2) Top/bottom.

(3) Bottom terminals protection screen as standard.