

SIRCOVER I - I+II - II

Rating (A)	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	Bridging bar	Auxiliary contact	Terminal shrouds	Terminal screens												
125 A	3 P	4190 3013 ⁽¹⁾	Black 4199 5012 ⁽²⁾	S2 type Black IP65 1423 2114 ⁽²⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽²⁾	4109 0019	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 2694 3014 ⁽⁴⁾⁽⁵⁾ 4 P 2694 4014 ⁽⁴⁾⁽⁵⁾	3 P 1509 3012 4 P 1509 4012												
	4 P	4190 4013 ⁽¹⁾																			
160 A	3 P	4190 3016 ⁽¹⁾																			
	4 P	4190 4016 ⁽¹⁾																			
200 A	3 P	4190 3019																			
	4 P	4190 4019																			
250 A	3 P	4190 3025 ⁽¹⁾				Black 4199 5012 ⁽²⁾		S2 type Black IP65 1423 2114 ⁽²⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽²⁾	4109 0025	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 2694 3021 ⁽⁴⁾⁽⁵⁾ 4 P 2694 4021 ⁽⁴⁾⁽⁵⁾	3 P 1509 3025 4 P 1509 4025								
	4 P	4190 4025 ⁽¹⁾																			
400 A	3 P	4190 3039 ⁽¹⁾								Black 4199 5012 ⁽²⁾		S2 type Black IP65 1423 2114 ⁽²⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽²⁾	4109 0039	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 2694 3021 ⁽⁴⁾⁽⁵⁾ 4 P 2694 4021 ⁽⁴⁾⁽⁵⁾	3 P 1509 3025 4 P 1509 4025				
	4 P	4190 4039 ⁽¹⁾																			
500 A	3 P	4190 3050 ⁽¹⁾												Black 4199 5012 ⁽²⁾		S2 type Black IP65 1423 2114 ⁽²⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽²⁾	4109 0050	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 2694 3051 ⁽⁴⁾⁽⁵⁾ 4 P 2694 4051 ⁽⁴⁾⁽⁵⁾	3 P 1509 3063 ⁽⁶⁾ 4 P 1509 4063 ⁽⁶⁾
	4 P	4190 4050 ⁽¹⁾																			
630 A	3 P	4190 3063 ⁽¹⁾	Black 4199 5012 ⁽²⁾	S2 type Black IP65 1423 2114 ⁽²⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽²⁾	4109 0063	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 2694 3051 ⁽⁴⁾⁽⁵⁾ 4 P 2694 4051 ⁽⁴⁾⁽⁵⁾	3 P 1509 3063 ⁽⁶⁾ 4 P 1509 4063 ⁽⁶⁾												
	4 P	4190 4063 ⁽¹⁾																			
800 A	3 P	4190 3080 ⁽¹⁾				Black 2799 7052 ⁽²⁾		S4 type Black IP65 1443 3114 ⁽²⁾	200 mm 1401 1520 320 mm 1401 1532 ⁽²⁾	4109 0080		1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 1509 3080 ⁽⁶⁾ 4 P 1509 4080 ⁽⁶⁾					3 P 1509 3080 ⁽⁶⁾ 4 P 1509 4080 ⁽⁶⁾			
	4 P	4190 4080 ⁽¹⁾																			
1250 A	3 P	4190 3120 ⁽¹⁾								Black 2799 7052 ⁽²⁾			S4 type Black IP65 1443 3114 ⁽²⁾	200 mm 1401 1520 320 mm 1401 1532 ⁽²⁾		4109 0120	1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾	3 P 1509 3080 ⁽⁶⁾ 4 P 1509 4080 ⁽⁶⁾		3 P 1509 3080 ⁽⁶⁾ 4 P 1509 4080 ⁽⁶⁾	
	4 P	4190 4120 ⁽¹⁾																			
1600 A	3 P	4190 3160 ⁽¹⁾	Black 2799 7052 ⁽²⁾	S4 type Black IP65 1443 3114 ⁽²⁾	200 mm 1401 1520 320 mm 1401 1532 ⁽²⁾						4109 0160					1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾		3 P 1509 3160 ⁽⁶⁾ 4 P 1509 4160 ⁽⁶⁾		3 P 1509 3160 ⁽⁶⁾ 4 P 1509 4160 ⁽⁶⁾	
	4 P	4190 4160 ⁽¹⁾																			
1800 A	3 P	4190 3180				Black 2799 7052 ⁽²⁾		S4 type Black IP65 1443 3114 ⁽²⁾	200 mm 1401 1520 320 mm 1401 1532 ⁽²⁾		4109 0160				1 st /2 nd contact NO/NC 4109 0021 ⁽³⁾			3 P 1509 3160 ⁽⁶⁾ 4 P 1509 4160 ⁽⁶⁾		3 P 1509 3160 ⁽⁶⁾ 4 P 1509 4160 ⁽⁶⁾	
	4 P	4190 4180																			

(1) Available enclosed (see "Enclosed changeover switches" page 625).

(2) Standard.

(3) 2 pieces supplied, one for position I and one for position II.

(4) To fully shroud front, rear, top and bottom 4 references required.

(5) To shroud front switch top and bottom 2 references required.

(6) 2 pieces supplied, one for top side and another for bottom side.