

References

Rating (A)	No. of poles	ATyS	ATyS d ⁽⁵⁾	Bridging bars	Terminal shrouds	Terminal screens	Auxiliary contact	3 position padlocking	Autotransformer										
125 A	3 P	9523 3012	9533 3012	4109 0019	3 P 2694 3014 ⁽²⁾ 4 P 2694 4014 ⁽²⁾	3 P 1509 3012 4 P 1509 4012													
	4 P	9523 4012	9533 4012																
160 A	3 P	9523 3016	9533 3016																
	4 P	9523 4016	9533 4016																
200 A	3 P	9523 3020	9533 3020							4109 0025	3 P 2694 3021 ⁽²⁾ 4 P 2694 4021 ⁽²⁾	3 P 1509 3025 4 P 1509 4025	1599 0002 ⁽⁴⁾	1599 0003 ⁽⁴⁾					
	4 P	9523 4020	9533 4020																
250 A	3 P	9523 3025	9533 3025																
	4 P	9523 4025	9533 4025																
315 A	3 P	9523 3031	9533 3031	4109 0039	3 P 2694 3051 ⁽²⁾ 4 P 2694 4051 ⁽²⁾	3 P 1509 3063 ⁽³⁾ 4 P 1509 4063 ⁽³⁾													
	4 P	9523 4031	9533 4031																
400 A	3 P	9523 3040	9533 3040																
	4 P	9523 4040	9533 4040																
500 A	3 P	9523 3050	9533 3050	4109 0050						3 P 2694 4051 ⁽²⁾	3 P 1509 4063 ⁽³⁾								
	4 P	9523 4050	9533 4050																
630 A	3 P	9523 3063	9533 3063	4109 0063	3 P 2694 4051 ⁽²⁾	3 P 1509 4063 ⁽³⁾													
	4 P	9523 4063	9533 4063																
800 A	3 P	9523 3080	9533 3080	4109 0080											3 P 1509 3080 ⁽³⁾ 4 P 1509 4080 ⁽³⁾	1599 0032 ⁽⁴⁾			400/230 VAC 1599 4064
	4 P	9523 4080	9533 4080																
1000 A	3 P	9523 3100	9533 3100	4109 0120						3 P 1509 3160 ⁽³⁾ 4 P 1509 4160 ⁽³⁾	1599 0004 ⁽⁴⁾								
	4 P	9523 4100	9533 4100																
1250 A	3 P	9523 3120	9533 3120	4109 0160	3 P 1509 3160 ⁽³⁾ 4 P 1509 4160 ⁽³⁾	1599 0004 ⁽⁴⁾													
	4 P	9523 4120	9533 4120																
1600 A	3 P	9523 3160	9533 3160	4109 0160											3 P 1509 3160 ⁽³⁾ 4 P 1509 4160 ⁽³⁾	1599 0004 ⁽⁴⁾			
	4 P	9523 4160	9533 4160																
1800 A	3 P	9523 3180	9533 3180							3 P 1509 3160 ⁽³⁾ 4 P 1509 4160 ⁽³⁾	1599 0004 ⁽⁴⁾								
	4 P	9523 4180	9533 4180																
2000 A	3 P	9523 3200	9533 3200		3 P 1509 3160 ⁽³⁾ 4 P 1509 4160 ⁽³⁾	1599 0004 ⁽⁴⁾													
	4 P	9523 4200	9533 4200																
2500 A	3 P	9523 3250	9533 3250	(1)											included	included			
	4 P	9523 4250	9533 4250																
3200 A	3 P	9523 3320	9533 3320							included	included								
	4 P	9523 4320	9533 4320																

(1) See "Copper bar connection kits" page 393.

(2) To fully shroud front, rear, top and bottom 4 references required.

To shroud front switch top and bottom 2 references required.

(3) 2 pieces: one for top side and another for bottom side.

(4) Factory mounting only.

(5) An optional key operated Auto/Manual selector is available on request.

If required, this option must be requested when ordering the switch;
 please refer to "Auto/Manual key selector" in the accessory section.

Technical information

- > Accessories: see page 392.
- > Characteristics: see page 398.
- > Terminals and connections: see page 400.
- > Dimensions: see page 402.