

## References

Rating (A)	No. of poles	ATyS g <sup>(5)</sup>	Bridging bars	Terminal shrouds	Terminal screens	Auxiliary contact	3 position padlocking	Autotransformer							
125 A	3 P	9553 3012	4109 0019	3 P 2694 3014 <sup>(2)</sup> 4 P 2694 4014 <sup>(2)</sup>	3 P 1509 3012 4 P 1509 4012	1599 0002 <sup>(4)</sup>	1599 0003 <sup>(4)</sup>	400/230 VAC 1599 4064							
	4 P	9553 4012													
160 A	3 P	9553 3016													
	4 P	9553 4016													
200 A	3 P	9553 3020													
	4 P	9553 4020													
250 A	3 P	9553 3025		4109 0025	3 P 2694 3021 <sup>(2)</sup> 4 P 2694 4021 <sup>(2)</sup>				3 P 1509 3025 4 P 1509 4025	1599 0002 <sup>(4)</sup>	1599 0003 <sup>(4)</sup>	400/230 VAC 1599 4064			
	4 P	9553 4025													
315 A	3 P	9553 3031		4109 0039											
	4 P	9553 4031													
400 A	3 P	9553 3040													
	4 P	9553 4040													
500 A	3 P	9553 3050	4109 0050	3 P 2694 3051 <sup>(2)</sup> 4 P 2694 4051 <sup>(2)</sup>	3 P 1509 3063 <sup>(3)</sup> 4 P 1509 4063 <sup>(3)</sup>	1599 0002 <sup>(4)</sup>	1599 0003 <sup>(4)</sup>	400/230 VAC 1599 4064							
	4 P	9553 4050													
630 A	3 P	9553 3063	4109 0063												
	4 P	9553 4063													
800 A	3 P	9553 3080	4109 0080						3 P 1509 3080 <sup>(3)</sup> 4 P 1509 4080 <sup>(3)</sup>				1599 0032 <sup>(4)</sup>	1599 0004 <sup>(4)</sup>	400/230 VAC 1599 4064
	4 P	9553 4080													
1000 A	3 P	9553 3100													
	4 P	9553 4100													
1250 A	3 P	9553 3120	4109 0120												
	4 P	9553 4120													
1600 A	3 P	9553 3160	4109 160	3 P 1509 3160 <sup>(3)</sup> 4 P 1509 4160 <sup>(3)</sup>	1599 0032 <sup>(4)</sup>					1599 0004 <sup>(4)</sup>	400/230 VAC 1599 4064				
	4 P	9553 4160													
1800 A	3 P	9553 3180													
	4 P	9553 4180													
2000 A	3 P	9553 3200	(1)			included	included	1599 0004 <sup>(4)</sup>				400/230 VAC 1599 4064			
	4 P	9553 4200													
2500 A	3 P	9553 3250													
	4 P	9553 4250													
3200 A	3 P	9553 3320													
	4 P	9553 4320													

(1) See "Copper bar connection kits" page 393.

(2) To fully shroud front, rear, top and bottom 4 references required.

To shroud front switch top and bottom 2 references required.

(3) 2 pieces: one for top side and another for bottom side.

(4) Factory mounting only.

(5) An optional key operated Auto/Manual selector is available on request.

If required, this option must be requested when ordering the switch; please refer to "Auto/Manual key selector" in the accessory section.

### Technical information

- > Accessories: see page 392.
- > Characteristics: see page 398.
- > Terminals and connections: see page 400.
- > Dimensions: see page 402.