




**Catalog Number:** LTAES07G-B  
**Product ID:** 7TAA012LB0R0006  
**UPC Number:** 78621010526  
**EAN Number:** 05415022389739  
**Status:** A



Liquid Tight Flexible Metallic Conduit, Aluminum Core with PVC Jacket, Conduit Size 2 Inch, Length 15 Meters/50 Feet, Working Temperature -20 to 80 Degrees C, Compliant to RoHS, Gray

Representative

Aluminum, CE compliant Liquid-tight Flexible Metallic Conduits provide excellent performance in corrosive environments and installations where lightweight wireway is required

- Full compliance to IEC 61386-1, -23 requirements, CE Certified
- Coordinated performance with Series 5200AL Fittings
- NEMA & IP ingress protection ratings aligned with industrial enclosures
- Smooth extruded jackets provide best performance with fittings
- Applications with light weight requirements, 40-50% lighter than typical steel construction
- Used extensively in applications where flexibility is necessary for motion, vibration and bending
- The inherent sunlight resistance of PVC enables this product to be used in outdoor applications
- Liquid-tight applications against water, oils, cutting fluids, mild acids
- For use in electrical circuits up to 1,000 volts

**North American Specifications (UNSPSC)**

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Type	Liquid Tight Flexible Metallic Conduit
Special Features	Designed to meet UL 360 ID/OD dimension requirements
Application	For Use in Corrosive Environments
Standard	RoHS
Trade Size	2 in
Outside Diameter	2.375 in
Inside Diameter	2.020 in
Length	50 ft ; 15 m
Radius	178 mm
Material	Aluminum
Finish	PVC Jacket
Color	Gray

**European Specifications (ETIM)**

ETIM	EC001179 Protective metallic hose
Nominal diameter	63mm
Nominal size in inch	2 inch
Outer diameter	60.33mm
Inner diameter	51.31mm
Material	Aluminium
Surface protection	Untreated
Sheathing material 1st coating	PVC
Operating temperature	-20-+80°C
Degree of protection (IP)	IP67
Weight	1.09kg/m



Colour	Grey
Bending strength	Flexible
Approved according to DIN EN 61386-23	Y
With approval according to UL	N
Approved according to CSA	N

### **Packaging**

Outer Quantity	50
Outer Dimensions (inches)	33.62x37x10.38
Weight Uom	0.96 lbs. Each

### **Documents / Support Tools**

Technical Drawing / Data Sheet	TDS000008
Technical Drawing / Data Sheet	TDS000117
Support/Tools	Available on Website
Catalog US	Available on Website