



Actual

Catalog Number: **SPLHC50/25M**
Product ID: 7TCA296030R0357
EAN Number: 05020963013775
Status: Active

Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 50mm, Outside Diameter 47.9mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

- Very high UV resistance
- Very High flexibility
- High fatigue life
- High mechanical strength
- Self extinguishing and halogen free
- Machine Building
- Extreme Temperature Environments

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39131706 Electrical conduit |
| IGCC | 5543 Liquid Tight Conduit |
| Brand Name | Adaptaflex |
| Type | Extreme Temperature Flexible Conduit |
| Application | Liquid Tight - Extreme Temperature Environments |
| Trade Size | 1-1/2 Inch/NC 50mm |
| Outside Diameter | 47.9mm |
| Inside Diameter | 40.4mm |
| Length | 25 Meters |
| Radius | 240mm |
| Flexibility | Medium |
| Material | Galvanized Steel Core with Thermoplastic Rubber Cover |
| Color | Black |

European Specifications (ETIM)

| | |
|--------------------------------|-----------------------------------|
| ETIM | EC001179 Protective metallic hose |
| Nominal diameter | 50mm |
| Outer diameter | 47.9mm |
| Inner diameter | 40.4mm |
| Material | Steel |
| Surface protection | Other |
| Sheathing material 1st coating | Other |
| Operating temperature | -65-+135°C |
| Degree of protection (IP) | IP68 |
| Weight | 1.15kg/m |
| Colour | Black |
| Bending strength | Flexible |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 1x1x1 |
| Weight Uom | 63.8 lbs. Each |

Header

| | |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com