



Catalog Number: CPO-A-1000-2-48
Product ID: 7TAA017320R0000
UPC Number: 78621081935
Status: A



Actual

Thin-Wall Heat Shrinkable Tubing, Red Polyolefin, 1 Inch, Shrink Ratio 3:1, Length 48 Inches, Operating Temperature -55 to 110 Degrees Celsius, Adhesive Lined

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Type	Heat Shrinkable Tubing
Shrink Ratio	3:1
Length	4 ft ; 1.22 m
Dielectric Strength	600 V/Mil (24kV/mm)
Volume Resistivity	1016 ohm-cm
Continuous Operating Temperature	-67 to +275 F ; -55 to +135 C
Minimum Shrink Temperature	248 F ; 120 C
Flammability	Flame Retardant
Water Absorption	0.20%
Color	Red

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	3:1
Inner diameter before heat-shrink	25.4mm
Inner diameter after heat-shrink	8.128mm
Nominal diameter inch	1 inch
Wall thickness after shrinking	2.54mm
Length	1.22m
Operation temperature	-55-+110°C
Colour	Red
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	Y
Printable	N
UL approval	N

Packaging

Outer Quantity	25
Outer Dimensions (inches)	6x51x6
Weight Uom	16 lbs. per 100