



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Brake Motors : Three-Phase - High Efficiency

Frame : 215T  
 Output : 3 HP  
 Frequency : 60 Hz  
 Poles : 8  
 Full load speed : 865 rpm  
 Slip : 3.89 %  
 Voltage : 230/460 V  
 Rated current : 8.66/4.33 A  
 Locked rotor current : 61.5/30.7 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.1  
 No-load current : 4.60/2.30 A  
 Full load torque : 18.0 lb.ft  
 Locked rotor torque : 200 %  
 Breakdown torque : 210 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 30 s (hot)  
 Service factor : 1.25  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 176 lb  
 Moment of inertia : 2.0244 sq.ft.lb  
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.76	84.0
75%	0.70	84.0
50%	0.59	82.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00309EP3EBM215T

Performed by

Checked