



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 213/5T
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1175 rpm
 Slip : 2.08 %
 Voltage : 208-230/460 V
 Rated current : 9.53-8.62/4.31 A
 Locked rotor current : 62.1/31.0 A
 Locked rotor current (I_L/I_n) : 7.2
 No-load current : 5.13/2.57 A
 Full load torque : 13.2 lb.ft
 Locked rotor torque : 180 %
 Breakdown torque : 290 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 90 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 172 lb
 Moment of inertia : 1.5268 sq.ft.lb
 Noise level : 55 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6308 ZZ	6207 ZZ	100%	0.71	90.2
Regreasing interval	---	---	75%	0.63	89.5
Grease amount	---	---	50%	0.51	87.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00312EG3E213T-W22

Performed by

Checked