



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 404/5T
 Output : 75 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1180 rpm
 Slip : 1.67 %
 Voltage : 208-230/460 V
 Rated current : 192-174/87.0 A
 Locked rotor current : 1340/670 A
 Locked rotor current (I_L/I_n) : 7.7
 No-load current : 62.5/31.3 A
 Full load torque : 329 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1257 lb
 Moment of inertia : 40.209 sq.ft.lb
 Noise level : 65 dB(A)

	D.E.	N.D.E.
Bearings	6217 C3	6314 C3
Regreasing interval	13507 h	14267 h
Grease amount	21 g	27 g

Load	Power factor	Efficiency (%)
100%	0.84	94.5
75%	0.81	95.0
50%	0.72	94.1

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #07512XT3E405T

Performed by

Checked